

Material Safety Data Sheet

Information on this form is furnished solely for the purpose of compliance with the Occupational Safety and Health Act and shall not be used for any other purpose. Waxman Consumer Products Group Inc. urges the customers receiving this Material Safety Data Sheet to study it carefully to become aware of the hazards, if any, of the product involved. In the interest of safety, you should notify your employees, agents, and contractors of the information on the sheet.

SECTION I - GENERAL INFORMATION				
Waxman Consumer Products Group Inc. 24455 Aurora Road Bedford Heights, OH 44146 Telephone No: 1-440-439-1830 Fax No: 1-440-439-1262	For chemical emergencies during transportation only call INFOTRAC 1-800-535-5053 24 hours per day - 7 days a week			
Date Prepared <p style="text-align: center;">1/1/02</p>	Trade Name <p style="text-align: center;">FLANGE & GASKET</p>			
SECTION II - HAZARDOUS INGREDIENTS / IDENTITY INFORMATION				
HAZARDOUS COMPONENTS	CAS#	APPROX%	ACGIH-TLV	OSHA-PEL
THIS PRODUCT IS NOT CLASSIFIED AS HAZARDOUS ACCORDING WITH OSHA 1910.1200.				
*Title III Section 313 Supplier Notification: this product contains toxic chemicals subject to the reporting requirements of Section 313 of the Emergency planning and community Right-to-Know Act of 1966 and of 40CFR372. This information must be included in all MSDS's that are copied and distributed for this material.				
<u>SHIPPING INFORMATION</u>	<u>SPECIAL HAZARD DESIGNATIONS</u>			
NOT HAZARDOUS FOR SHIPPING PURPOSES.				
		<u>HMIS</u>	<u>NFPA</u>	<u>HAZARD RATING</u>
	HEALTH	0	0	0 - MINIMAL
	FLAMMABILITY	1	1	1 - SLIGHT
	REACTIVITY	0	0	2- MODERATE
	PROTECTIVE			3- SERIOUS
	EQUIPMENT	X	X	4- SEVERE
SECTION III - PHYSICAL DATA				
APPEARANCE <p style="text-align: center;">SOLID AMBER</p>	ODOR <p style="text-align: center;">NEARLY ODORLESS</p>	BOILING POINT <p style="text-align: center;">N/A</p>		
SPECIFIC GRAVITY (H₂O=1) <p style="text-align: center;">.85</p>	VAPOR PRESSURE (mm Hg.) <p style="text-align: center;">NIL</p>	VOLATILE BY VOLUME (%) <p style="text-align: center;">NIL</p>		
VAPOR DENSITY (AIR=1) <p style="text-align: center;">10+</p>	EVAPORATION RATE (BUAC=1) <p style="text-align: center;">N/A</p>	SOLUBILITY IN WATER <p style="text-align: center;">NIL</p>		

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT (METHOD USED) 500°F MIN P.M.	FLAMMABLE LIMITS (PERCENT BY VOLUME)	LEL	UEL
		ND	ND

FIRE EXTINGUISHING MEDIA
CARBON DIOXIDE, FOAM, DRY CHEMICAL.

SPECIAL FIRE FIGHTING PROCEDURES
DO NOT USE WATER AS IT MAY BE INEFFECTIVE IN EXTINGUISHING A FIRE INVOLVING THIS MATERIAL.

UNUSUAL FIRE AND EXPLOSION HAZARD
NONE

SECTION V - HEALTH HAZARD DATA

PRIMARY ROUTES OR ENTRY Inhalation Skin contact Eye contact Ingestion

EFFECT OF OVEREXPOSURE
MIGHT IRRITATE SKIN.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE
SKIN DISORDERS.

EMERGENCY AND FIRST AID PROCEDURES
SWALLOWING - NONE NECESSARY. SKIN - NONE NECESSARY AS A SOLID. CONTACT WITH MELTED PETROLATUM CAN CAUSE THERMAL BURNS, FLUSH WITH WATER TO COOL AFFECTED AREAS AND CONTACT A PHYSICIAN IMMEDIATELY. INHALATION - REMOVE TO FRESH AIR, CALL A PHYSICIAN. EYES - FLUSH WITH WATER, CALL A PHYSICIAN.

SECTION VI - REACTIVITY

STABILITY	UNSTABLE		CONDITIONS TO AVOID EXCESS HEAT, DIRECT FLAME.
	STABLE	X	

INCOMPATIBILITY (MATERIALS TO AVOID)
STRONG OXIDIZERS.

HAZARDOUS DECOMPOSITION PRODUCTS
COMBUSTION WILL PRODUCE CARBON MONOXIDE AND OTHER ASPHYXIANTS.

HAZARDOUS POLYMERIZATION	MAY OCCUR		CONDITIONS TO AVOID NONE KNOWN.
	WILL NOT OCCUR	X	

SECTION VII - SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

RECOVER FREE SOLID. IF MOLTEN PARAFFIN SPILLED, SOLDIFY AND RECOVER.

WASTE DISPOSAL METHOD

INCINERATE PER LOCAL, STATE AND FEDERAL REGULATIONS.

SECTION VIII - SPECIAL PROTECTION INFORMATION**RESPIRATORY PROTECTION (Specify type)**

N/A

VENTILATION

N/A

PROTECTIVE GLOVES

N/A

EYE PROTECTION

N/A

OTHER PROTECTIVE EQUIPMENT AND HYGIENIC PRACTICES

N/A

SECTION IX - SPECIAL PRECAUTIONS**PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING**

AVOID EXCESSIVE HEAT OR DIRECT FLAME.

OTHER PRECAUTIONS

WHEN DEALING WITH HOT MELTED PETROLATUM, SPECIAL PRECAUTIONS PERTINENT TO YOUR OPERATION SHOULD BE AS FOLLOWED. AS WITH ANY PETROLEUM HYDROCARBON, PERSONAL HYGIENE IS IMPORTANT TO ASSURE THAT PROLONGED OR REPEATED CONTACT IS MINIMIZED. HANDS AND OTHER EXPOSED AREAS SHOULD BE WASHED THOROUGHLY WITH SOAP AND WATER AFTER CONTACT, ESPECIALLY BEFORE EATING AND OR SMOKING.

This information contained herein is based on data considered accurate. However, no warranty is expressed or implied regarding the accuracy of this data or the results to be obtained from the use thereof.